

HIGHEST QUALITY OF YOUR PRODUCT ENSURED WITH RIGHT MEASURING INSTRUMENTS.

TORQUE METERS

ELECTRIC SCREW DRIVER HIGH TORQUE



- Auto power OFF
- One-touch zero adjustment
- RS232C output (computer management about data.)
- High and low limits judging function.
- A setup is possible respectively in a maximum value and a minimum value. GOOD/NG is checked with an LED lamp.



(GOOD)



(NG)

- Display and Preservation of Maximum, Minimum Value, and Average.
- Measurement by the side of rewinding (CCW) can be performed.
- About the load torque under measurement, it is a data output at real time (every about 1 / 100 seconds).
- The printable character became legible greatly.
- The memory of a maximum of 400 data is possible. The data control in a personal computer is easily by the RS232C output.
- Uses by battery drive, being unable to choose a place, and convenient for carrying by the spot

Specification		DI-11
Measuring range (at the time of Track)		0.10 ~ 20 N·m
		1.0 ~ 200 kgf· cm
		1.0 ~ 180 lbf· in
Accuracy		±0.5% (F/S) (499 or less digit±3digit)
Display		The 4 figures digital display of LED
The measurement direction		CW-CCW (right and left)
Measuring mode	P-P Peak	Peak load value hold.
	T-R Track	Indication of real time torque value.
	P-D Peak down	Holding Load Value at the moment to change from upward to downward

Specification	DI-11
High and low limits judging function	High and low value are measurement within the limits, and can be set up.
The Maximum, the minimum, and the average value display	The maximum, the minimum, average value, and the data number of 30 data are displayed. It saves to ten channels.
Automatic Clearance	Automatically clear the displayed value after certain time (0.5 - 3.0 sec).
One-touch zero	A clear button is pushed and it is a zero. Data is outputted.
Data output	RS232C conformity (baud rate 9600)
Power supply	Ni-Cd chargeable battery 1.2Vx5cells 700mAh
Auto power save	10 minutes no use, automatically switch off.
Charging time	From empty - less than 6hours
Continuous working time	12 hours
Socket fit mouth	20mm/ 9.5mm
Weight	Abbreviation 1.5 kg
Outside dimension	130 (W) ×180 (D) ×34 (H)
Attachment	Measurement joint SJ-50 / SJ-100
OPTIONAL	Data Cable
Accessories (one piece each)	AC/DC adaptor (230V.)
	Exclusive receipt case
	An inspection report, a proofreading certificate, traceability system figure



www.advancetechonline.in

ADVANCE TECH SERVICES PVT. LTD. 709-710, GD-ITL Towers, B-8, Netaji Subhash Place, Pitampura, Ring Road, New Delhi 110 034 Ph : 011-47002024 upto 27, Fax : 011-47002029E-Mail : info@advancetechonline.in web:www.advancetechonline.in **B.O : • Bangalore • Pune**

PRODUCT RANGE: Soldering Desoldering for SMD/PTH, Solder POT, Electric Screw Drivers, Pneumatic Screw Driver, Torque Meter, Screw Torque deciders, Screw Feeders, Balancer, Torque Arm, Air Dispenser, Air Free Dispenser, Syringes and Barrel for dispenser, Flux, Spray Fluxer, Desolder Wick, Static Charge Meter, Ionizers, Ion Gun, Illuminated Magnifiers, Hand tools (Cutter, strippers, Pliers, crimpers, Cable cutters etc.. ESD Products, Peelable Mask, Solder Bath Treatment, Rework Pens (Conductive pen, flux pen, green over coat pen, conformal coating remover pen), Imported stations soldering bits, Bit Cleaning sponge, Screw driver bits and many more.....