

Anti-Static Temp. Control Soldering Station. MODEL NO. : RX701AS

Features/Specification :

- Input 220-240V AC, Power Consumption 65W.
- Body made from anti-static material
- Temperature Range 200-450°C.
- Insulation Resistance over 100 M
- Dimension :
Control Unit 146 (L) x 115 (W) x 98 (H) mm
Soldering Unit 195 mm, Weight : Control Unit 1.5 kg,
Soldering Unit 41 gm.
- Ripple Temp. Without Load $\pm 3^{\circ}\text{C}$,
- Leakage voltage under 0.5 mV,
- Ground Resistance Under 2
- Ultra long life tips in variety of shape.
- Zero volt switching ensure low noise & keeps tip temp. stable.
- Protective cover prevent accidental temperature change.
- High Efficiency NEW circuit design.
- 60 Watt high capacity Ceramic Heater with connector & easy to replace.



Anti-Static Digital Display Temp. Control Soldering Station. MODEL NO. : RX-711AS

Features/Specification :

- Input 220-240V AC, Power Consumption 65W.
- Body made from anti-static material
- Temperature Range 200-480°C.
- Insulation Resistance over 100 M
- Dimension :
Control Unit 146 (L) x 115 (W) x 98 (H) mm,
Soldering Unit 195 mm, Weight : Control Unit 1.5 kg,
Soldering Unit 41 gm.
- Ripple Temp. Without Load $\pm 3^{\circ}\text{C}$,
- Leakage voltage under 0.5 mV,
- Ground Resistance Under 2
- Ultra long life tips in variety of shape.
- Zero volt switching ensure low noise & keeps tip temp stable.
- Protective cover prevent accidental temperature change.
- High Efficiency NEW Circuit Design.
- 60 Watt high capacity Ceramic Heater with connector & easy to replace.



Economical Temp. Control Soldering Station. MODEL NO. : PX-501

Features/Specification :

- Input 220-240V AC, Power Consumption 85W.
- Temperature Range 250-450°C.
- Insulation Resistance over 100 M
- Dimension : Control Unit 85 (L) x 100 (W) x 57 (H) mm, Soldering Unit 220 mm,
- Weight : Control Unit 267gm, Soldering Unit 41 gm.
- Ripple Temp. Without Load $\pm 3^{\circ}\text{C}$, Leakage voltage under 0.1 mV,
- Ground Resistance Under 0.3
- Ultra long life tips in variety of shape.
- Zero volt switching ensure low noise & keeps tip temp. Stable.
- 80 Watt high capacity Ceramic Heater with connector & easy to replace.



Optional stand

From goot Japan Warranty:1 year AMD

Economical Anti-Static Temp. Control Soldering Station PX-501AS.

Features/Specification :


- Input 220-240V AC, Power Consumption 85W.
- Temperature Range 250-450°C.
- Insulation Resistance over 100 M
- Dimension : Control Unit 85 (L) x 100 (W) x 57 (H) mm, Soldering Unit 220 mm,
- Weight : Control Unit 267gm, Soldering Unit 41 gm.
- Ripple Temp. Without Load $\pm 3^{\circ}\text{C}$, Leakage voltage under 0.1 mV,
- Ground Resistance Under 0.3
- Ultra long life tips in variety of shape.
- Zero volt switching ensure low noise & keeps tip temp. Stable.
- 80 Watt high capacity Ceramic Heater with connector & easy to replace.



Optional stand

From goot Japan Warranty:1 year AMD

Soldering Tips for RX-711AS, RX-701AS, PX-501, PX-501AS



Web : www.advancetechonline.in

ADVANCE TECH SERVICES PVT. LTD. 709-710, GD-ITL Towers, B-8, Netaji Subhash Place, Pitampura, Ring Road, New Delhi 110 034
Ph : 011-47002024 upto 27, Fax : 011-47002029E-Mail : info@advancetechonline.in web:www.advancetechonline.in B.O : • Bangalore • Pune

PRODUCT RANGE: Soldering Desoldering for SMD/PTH, Solder POT, Electric Screw Drivers, Pneumatic Screw Driver, Torque Meter, Screw Torque deciders, Screw Feeders, Abalancer, Torque Arm, Desk top and Scara robots, dispensing robots, Air Dispenser, Air Free Dispenser, Syringes and Barrel for dispenser, Flux, Spray Fluxer, Desolder Wick, Stencil wipe rolls, Static Charge Meter, Ionizers, Ion Gun, Illuminated Magnifiers, Hand tools (Cutter, strippers, Pliers, crimpers, Cable cutters etc.. ESD Products, Peelable Mask, Solder Bath Treatment, Rework Pens (Conductive pen, flux pen, green over coat pen, conformal coating remover pen), Imported stations soldering bits, Bit Cleaning sponge, Screw driver bits and many more.....